

CASIO® TE-2400

Simple, yet powerful cash register to help you manage your hospitality business transactions



www.casio.co.uk/systems

CASIO®

The Casio TE-2400 features a 77 key fully flat keyboard for fast order registering, high speed dual printers and a bright customer display making it ideal for the hospitality environment.

CASIO® TE-2400

Receipt and journal printer



The TE-2400's two fast, 58mm wide thermal printers can print at up to 14 lines per second. To give your business a professional appearance, graphic logos and watermarks can also be printed. With easy drop-in paper loading for roll replacement, the TE-2400 ensures fast and efficient operation.

Table control function

A basic table control function is provided for small restaurants, cafes and bars. Purchased items can be input against a table number, allowing easy check tracking.

By attaching the TE-2400 to a remote kitchen printer, food orders can automatically be printed in the kitchen, maximising order preparation time.

Barcode scanning

The TE-2400 supports barcode scanning. This allows up to 5000 products to be scanned into the cash register, ensuring items are sold at the correct price and eliminating the need to manually enter prices.

Display

A bright, contrast adjustable 5.2-inch LCD operator display with large price display and 2 lines for other product information, means your staff can easily see the details of the items they are selling. A standard pop-up rear display ensures your customers can see the price they are paying, giving them peace of mind.



Help function

The TE-2400 is simple to operate, however there is also a user friendly "HELP" button on the keyboard. Answers to frequently asked questions such as how to programme the time and date can be printed on the receipt printer for easy reference.



Peripherals

For maximum flexibility, the TE-2400 features two serial ports for direct connection to PC, modem, printers or scanners.

Reports and useful functions

Daily reports can be printed on the TE-2400 using compressed printing. Other useful functions include clerk interrupt, scheduler function, set menu function, arrangement function and memory allocation.

- Financial
- Transaction
- Department
- PLU
- PLU stock
- Table analysis
- Open check
- Monthly
- Hourly
- Flash
- Group
- Clerk
- Time & attendance
- Scanning PLU
- Scanning PLU stock
- Inactive PLU

Z	10-10-2012	21:10	Mode symbol/date/time
C01	MC#01	000045	Clerk descriptor/Mc-No./consecutive No.
Z	SCAN PLU	0001	Report header/title/reset counter (Z only)
		2001026	Report code
DEPT01	01	Classified title(by group/dept)
SCAN_PLU001		382	Scanning PLU character/quantity
		17.07%	Sales ratio/total
	#4901234567894		Scanning PLU code
SCAN_PLU002		382	
		38.01%	
	#4989012345674		
SCAN_PLU003		382	
		10.49%	
	#4967890123454		
		1253	Total of this classification
		9,275.83	
DEPT02	02	
SCAN_PLU010		453	
		1,583.47	
	#4945678901234		
		243	
		10,375.93	
TL		12653	Quantity total
		273,375.93	Amount total

Data storage

The TE-2400 features a Compact Flash (CF) card slot, which allows reports to be saved to a CF card for easy transferral to PC for manipulation with other software. Program data can also be stored for backup purposes.

Options

Model No.	Product
SP-1300	Slip Printer
UP-360	External Printer (thermal)

Specifications

Operator	5.2-inch backlit LCD
Displays	2 x 16 characters / 10 digits, 7 segments
Customer	Pop-up 8-digit numeric
Printer	Printing method Two-station thermal printer
	Printing speed 14 lines/sec. (max.)
	Paper width 58mm +0/-1mm x 80
	Paper loading Drop-in paper loading
Memory back-up	90-day data backup (vanadium lithium battery)
Power consumption	AC 230V: Operating 0.25A, Standby 0.05A
Operating environment	Temperature: 0 to 40°C
	Humidity: 10 to 90%RH
Dimensions (w/ med. drawer)	277 (H) x 400 (W) x 450 (D) mm
Weight (w/ med. drawer)	Approx. 12 kg

Specifications and design are subject to change without notice

www.casio.co.uk/systems

For more information, please call a member of our sales team on 01903 218700 or order on-line at www.till-rolls.com

CASIO®